



TYP	Waga kg	Wymiary (mm)																		
		D1	D2	L1	L2	L3(E)	L3(H)	L3(L)	L4	L6	L7	L8	L9	H1	H2	H3	W1	W2	HEB	Loch-Ø
SB 300	250	152	280	500	135	1350	-	1450	385	80	540	80	20	100	215	520	500	460	100	14
SB 301	250	191	340	500	155	1350	-	1450	405	80	540	80	20	100	215	520	500	460	100	14
SB 304	400	241	430	500	155	1600	1350	1650	405	80	550	80	20	100	260	610	600	560	100	14
SB 305	400	273	490	500	155	1650	1350	1800	405	80	550	80	20	100	260	610	600	560	100	14
SB 306	510	324	580	500	165	1700	1450	1850	415	80	560	80	20	100	310	710	700	660	100	18
SB 307	790	394	680	500	200	1950	1550	1900	450	100	560	100	25	120	360	830	800	750	120	20
SB 309	1100	419	730	500	230	2000	1550	1900	480	110	560	110	30	140	435	1000	1000	940	140	22
SB 310	1420	495	860	500	235	2100	1600	1950	485	120	590	120	40	160	460	1070	1100	1040	160	26
SB 311	1740	546	960	500	259	2150	1600	1950	509	120	590	120	40	160	510	1170	1150	1090	160	30
SB 313	2320	572	1020	500	260	2150	1700	1950	510	120	590	120	40	180	585	1340	1350	1280	180	32
SB 315	3400	711	1350	500	299	2600	2050	-	549	140	590	140	40	200	685	1560	1550	1470	200	36
SB 316	2900	711	1400	500	299	2650	2100	-	549	140	590	140	40	200	710	1610	1600	1520	200	36

typ SB 307 SB z nap dem umieszczonym pod k tem

